

SWAROVSKI ETERNAL011102A Comfort single Lever Basin Mixer

INSTALLATION INSTRUCTION


****ACCESSORIES CHECKING**

LIST OF THE STANDARD ACCESSORIES:

Please double-check the accessory list hereinafter and contact our company or our distributor for any unconformity.

Remarks:


- 1. Without affecting their performancing, accessories may be changed without further notice;
- 2.Drawings for reference only, product size & shape refer to actual.





Accessories list		
No.	Name	Qty
1	Handle	1
2	Screw	1
3	Index	1
4	Dome	1
5	O-ring	1
6	Nut	1
7	Cartridge	1
8	Main body	1
9	Aerator assembly	1
10	O-ring	1
11	Fixed assembly	1
12	Inlet hose	2


Installation Instructions


- ☆ Do not disassemble the main body, as it has been installed & commissioned correctly & precisely before leaving the factory;
- ☆ To avoid the faucet from jamming, do flush the water pipe before installation;
- ☆ After installation, make sure every joint safely sealed & no leaking;
- ☆ Using condition: Working pressure at 0.05-1.0MPa(including cold & hot water pressure), with applicable water temperature: 4°C-90°C;
- Make sure to connect the hot/cold inlet pipe correctly, if standing in front, hot water pipe connecting to the left & cold water pipe connecting to the right.















WUsage

☆How to operate the handle

1.Raise the handle up for opening water, push it down for close; 2.Turn the handle to the left to increase hot water flow for higher water temperature, and lower water temperature by operating reversely.



Cleaning & Maintenance

- ☆ To keep the product clean & shining, follow as below:
 - 1.Flush with clean water & dry with soft cloth only;
 - 2.If any dirt, clean with soft liquid or transparent glass detergent;
 - 3.Do not use any scrubbing detergent, polisher, sane-cloth, paper tissue or scraper;
 - 4.Do not use acid detergent, insoluble grain-like detergent or soap;
 - 5. Circumrotate the aerator off and clean it when necessary.

