

# SKY 11 1101 Standard Single Lever Digital Display Basin Mixer

# INSTALLATION INSTRUCTION


#### **XACCESSORIES CHECKING**

LIST OF THE STANDARD ACCESSORIES:

Please double-check the accessory list hereinafter and contact our company or our distributor for any unconformity.

#### Remarks:


- 1. Without affecting their performancing, accessories may be changed without further notice;
- 2.Drawings for reference only, product size & shape refer to actual.




Accessories list		
No.	Name	Qty
1	Main body	1
2	O-ring	1
3	Fixed assembly	1
4	Inlet hose	2


#### \*Installation Instructions


- ☆ Do not disassemble the main body, as it has been installed & commissioned correctly & precisely before leaving the factory;
- ☆ To avoid the faucet from jamming, do flush the water pipe before installation;
- ☆ After installation, make sure every joint safely sealed & no leaking;
- ☆ Using condition: Working pressure at 0.05-1.0MPa(including cold & hot water pressure), with applicable water temperature: 4°C-90°C;
- ☆ Make sure to connect the hot/cold inlet pipe correctly, if standing in front, hot water pipe connecting to the left & cold water pipe connecting to the right.







#### **X** Installation Procedures










### **XUsage**



### ※ Cleaning & Maintenance

- ☆ To keep the product clean & shining, follow as below:
  - 1.Flush with clean water & dry with soft cloth only;
  - 2.If any dirt, clean with soft liquid or transparent glass detergent;
  - 3.Do not use any scrubbing detergent, polisher, sane-cloth, paper tissue or scraper;
  - 4.Do not use acid detergent, insoluble grain-like detergent or soap;
  - 5. Circumrotate the aerator o ffand clean it when necessary.

